



# CPM System Specifications Sheet

The SAMPI CPM's are complete truck pumping and metering integrated systems, which can operate with PTO or hydraulic motors. These systems comprise a multi-way valve for loading/unloading modes. CPM systems are ideal where terminals are not provided with a pumping and/or metering system.



## Main features

- Suction from tank, pumping and metered delivery (through the meter)
- Suction from tank, pumping and unmetered delivery (by-passing the meter)
- External suction, pumping and return into tank
- Suction and pumping from/to external tank
- Flow-rate regulation

## Specifications

| Model  | Flow rate<br>l/min (GPM) | Pump  | Meter |
|--------|--------------------------|-------|-------|
| CPM350 | 350 (92)                 | RVP25 | M-7   |
| CPM700 | 700 (185)                | RVP30 | M-15  |

## Dimensions

| Model   |    | L     | W     | H     |
|---------|----|-------|-------|-------|
| CPM350  | mm | 1020  | 510   | 610   |
|         | in | 40.13 | 20.06 | 24.00 |
| CPM700  | mm | 1250  | 550   | 650   |
|         | in | 49.17 | 21.64 | 25.57 |
| Cabinet | mm | 1300  | 650   | 685   |
|         | in | 51.14 | 25.57 | 26.95 |

### **SAMPI spa**

A unit of IDEX Corporation  
Via Amerigo Vespucci, 1  
55011 Altopascio (Lucca) – Italy  
Phone: +39 0583 24751  
Fax: +39 0583 264748  
[www.sampi.it](http://www.sampi.it)

